Emergency Switch

Specifcation Sheet

Features

- Single-gang mounting
- 2 or 4 pole switches
- Attractive, flame-retardant (UL® 94V-0) plastic panel
- Highly visible emergency labeling
- May use with a central annunciator, or for local alarm functions

Description

The SF117-series Emergency Call Switch is available in two models and features a rugged, long-life, positive-acting switch mounted on a durable flame-retardant (UL® 94V-0) plastic panel. Signaling an emergency requires just a short pull in any direction on the 6' long nylon cord. The signal cannot be canceled except at the point of origin. The SF117/2C provides two circuits to operate a separate visual and audible signal. The SF117/4C provides two additional circuits that may be used to operate additional signaling devices as needed.

Specifications

Dimensions:	Height:	4.5"	(114 mm)
	Width:	2.75"	(70 mm)
	Depth:	1.5"	(38 mm)
Panel:	Flame-retardant (UL® 94V-0) plastic		
Switch:	SF117/2C—2PDT		
	SF117/4C—4PDT		
Connection:	Wire leads		
Mounting:	Standard single-gang electrical box		
Marking:	Pad-printed **EMERGENCY**		

CONTROLLEDCARE SYSTEMS

305-109 Railside Road

Toronto, ON, M3A1B2, Canada

Emergency Sliding Switch

Required Components

Solution:
Advanced I/O Controller

Solution:
Wired Nurse Call System Solution

2002-2018 © Copyright - ControlledCare Health Solutions, a Vantact.com Information Systems company.