

WIRELESS DRY CONTACT SENSOR

The wireless dry contact sensor detects a connection between two wires. When the wires are either shorted or opened, an alert is sent over the wireless network. Versions of the sensor support the major wireless standards such as 433MHz, LoRa/LoRaWAN, and Wi-Fi.

Indoor / Smart Building



APPLICATIONS

- Detect connection of dry contacts, relays, etc
- Doorbell press detection
- Remote button press detection
- Remote reed switch detection
- General purpose contact sensor (two wire open/close detection)

CONTROLLED CARE SYSTEMS

305-109 Railside Road
Toronto, ON, M3A1B2, Canada

Outdoor / Industrial



FEATURES

- Built-in radio that talks directly with the wireless network*. Standards include:
 - RF 433MHz®
 - LoRa®/LoRaWAN™
 - Wi-Fi
- Two types of tamper detection: enclosure tamper and wall mount tamper
 - Enclosure tamper detects if the packaging of the sensor itself is opened or broken
 - Wall mount tamper detects (indoor version only)
- 20,000-200,000+ transmissions on a single battery and a 5-10 year battery life depending on usage
- User replaceable battery
- Fully integrated internal antenna
- Over the air sensor configuration in the field
- Automatic low battery reporting and supervisory (sensor health) reporting
- IP67 Armored Sensor™ version for outdoor/industrial use